liquid lubricants/greases

Since 1927, Arrow-Magnolia has helped people solve their cleaning and maintenance problems with the finest products available today.

ARROW-MAGNOLIA International, Inc.

CD-80

HIGHLIGHTS

- Liquid Corrosion Resistant
- Rapid Penetration
- Leaves Protective Coating
- Eliminates Fire Hazards Caused By Flammable Penetrants

TYPICAL PROPERTIES

- Vapor Pressure: **13**
- Volatility: **88**
- Solubility: **Yes**
- Specific Gravity: **1.419**
- Vapor Density: **N/A**
- pH: **N/A**
- Evaporation Rate: **Slower than Ether**
- Physical Description: **Clear amber liquid w/ chlorinated solvent odor**

SAFETY CAUTIONS

- Keep out of reach of children.
- Keep containers closed when not in use.
- Use under normal atmospheric conditions in well-ventilated areas.
- Refer to MSDS for additional safety information.

HMIS RATINGS



Liquid

DESCRIPTION:

CD-80 is a penetrant and release agent that loosens bolts, fittings and pins for quick, easy removal. It is excellent for use on bearings, electrical switch gears, textile machines and printing presses. The protective coating resists corrosion and makes tools and machinery last longer.

DIRECTIONS:

CD-80 can be applied by brushing, spraying or immersion procedures. For brush application, transfer a small amount of CD-80 to a suitable container and brush on metal surfaces involved. For spraying, use a hand operated sprayer or a three gallon sprayer for large surface areas. For miscellaneous small parts, a six gallon metal container equipped with a metal dip basket provides the optimum treatment procedure. The parts are placed in the metal dip basket, immersed in the CD-80 for 2-3 minutes, removed and drained. The parts are now ready for storage or further processing.

manufactured by:

ARROW - MAGNOLIA INTERNATIONAL, Inc.
2646 Rodney Lane
Dallas, Texas 75229
Toll Free: 800.527.2101
Fax: 972.484.2896
www.arrowmagnolia.com

LG-2050/0512