liquid cleaners/degreasers

Since 1927, Arrow-Magnolia has helped people solve their cleaning and maintenance problems with the finest products available today.

ARROW-MAGNOLIA International, Inc.

Since 1927

SEAL STRIP

Liquid

HIGHLIGHTS

- Removes Organic Seal Coatings
- Non-Corrosive
- Fast, Effective Stripping Action

TYPICAL PROPERTIES

- Vapor Pressure: **340**
- Volatility: **89**
- Solubility: **Yes**
- Specific Gravity: **1.205**
- Vapor Density: **N/A**
- pH: **N/A**
- Evaporation Rate: **Slower than ether**
- Physical Description: **Cloudy liquid w/chlorinated solvent odor**

SAFETY CAUTIONS

- Keep out of reach of children.
- Store in closed, labeled containers.
- Store in cool, dry area away from heat and open flames.
- Refer to MSDS for additional safety information.

HMIS RATINGS



DESCRIPTION:

SEAL STRIP was designed specifically for the removal of organic seal coatings. Will safely remove paint, enamel, lacquer, shellac, varnish, reflective coatings, etc. from wood, metal, plaster or masonry. Works fast and will remove many coats with one application. Will not raise grain or remove stain from wood. Do not use on linoleum or other synthetics.

DIRECTIONS:

Brush Applications: Lay on with a full brush. Brush in one direction only. Leave on from 5 to 30 minutes, depending upon thickness and age of material to be removed. After finish blisters, remove by scraping, wiping or flushing with a high pressure water spray. Dip steel wool in stripper and scrub for final touch up.

Immersion Application: Immerse article completely in stripper. Remove and allow stripper to work on film for 5 to 30 minutes dependent upon thickness and age of film. When old finish "peels away" as evidenced by blistering and wrinkling, flush with a high pressure water spray. Touch up with steel wool dipped in stripper. Cover immersion tank when not in use.

manufactured by:

ARROW - MAGNOLIA INTERNATIONAL,Inc.
2646 Rodney Lane
Dallas, Texas 75229
Toll Free: 800.527.2101
Fax: 972.484.2896
www.arrowmagnolia.com

CD-6280/0910