

# aerosol lubricants/greases

Since 1927, Arrow-Magnolia has helped people solve their cleaning and maintenance problems with the finest products available today.

**ARROW-MAGNOLIA**  
**INTERNATIONAL, INC**



SINCE 1927

## TYPICAL PROPERTIES

- Premium Penetrating Lubricant & Release Agent
- Excellent Water Displacement
- Non Flammable
- Spray any way Valve
- Dissolves Rust & Corrosion Instantly
- Quickly Penetrates Through Grease, Oil, & Soils
- Lubrication Provided by PTFE
- 9Vt bca JW'' & \$' cn '7Ub

## HIGHLIGHTS

- Vapor Pressure: **59**
- Volatility: **B#5**
- Solubility: **Yes**
- Specific Gravity: **1.65**
- Vapor Density: **>2**
- pH: **N/A**
- Evaporation Rate: **B#5**
- Physical Description: 'CdUei Y' **Bfck b 'SdfUnz'w/ M]bhand' Sc:j YbhOXcf'**

## SAFETY CAUTIONS

- Keep out of reach of children.
- Do not puncture or incinerate containers.
- Do not store at temperatures above 130°F.
- Avoid food contamination
- Avoid breathing vapors.
- Remove ignition sources.
- Refer to SDS for additional safety information.



## HMIS RATINGS

Flammability	1	0	Reactivity
Health	2	C	
Personal Protection			



# CD-80

## AEROSOL DESCRIPTION:

CD-80 will loosen rust instantly to free frozen nuts, bolts, and fittings without damage to the metal. Penetrates deeply into close tolerance critical areas to free even counter sunk bolts.

CD-80's strong solvent based formula penetrates through water, grease, oil, and other soils quickly working faster to save time and labor. Contains PTFE to help coat metal surfaces to prevent further rust and corrosion.

In some cases with severe rust and corrosion a torch is used, and many penetrating fluids are flammable which creates a more hazardous situation. CD-80 is a non-flammable, premium penetrating lubricant making it a safer product to use in the workplace. Large 20 oz cans make CD-80 more economical to use.

## DIRECTIONS:

-Hold container upright 6 to 8 inches from the surface to be sprayed. Spray area to be treated liberally and allow sufficient time for complete penetration, 20 to 30 seconds.

-For extremely rusted and corroded parts additional product made be used and tapping or heating may be required.

-Note: when changing the spray nozzle or inserting the extension tube always point the arrow on the spray nozzle away from your face and eyes.

distributed by:  
ARROW - MAGNOLIA INTERNATIONAL, Inc.  
2646 Rodney Lane  
Dallas, Texas 75229  
Toll Free: 800.527.2101  
www.arrowmagnolia.com