Since 1927, Arrow-Magnolia has helped people solve their cleaning and maintenance problems with the finest products available today.

#### HIGHLIGHTS

- -Multi Purpose NLGI #2 Bentone Based Grease
- -Penetrates & Quickly Sets Up
- -Withstands Extreme

Temperatures To 500°F

- -Handles Extreme Pressure & Heavy Loads
- -Superior Water Resistance
- -Non Chlorinated

#### **SAFETY CAUTIONS**

-Vapor Pressure: 25-46

-Volatility: B#5

-Solubility: Insc`i V`Y

-Specific Gravity: **0.81** 

-Vapor Density: N/A

-pH: **N/A** 

-Evaporation Rate: B#5

-Physical Description. 'Red

Grease w/Sc'j Ybh'OXcf'

#### SAFETY CAUTIONS

- -Keep out of reach of children.
- -Do not puncture or incinerate containers.
- -Do not store at temperatures above 130 ° F.
- -Avoid breathing vapors.
- -Refer to SDS for additional safety information.



#### **HMIS RATINGS**

Flammability

Health 2 0 Reactivity



Personal Protection

# ARROW-MAGNOLIA INTERNATIONAL, INC

**SINCE 1927** 

### **INSTA-LUBE**

## AEROSOL **DESCRIPTION:**

INSTA-LUBE is a multi-purpose, heavy load, high temperature No. 2 red grease in a convenient easy to use aerosol. The product is extremely versatile and can be used on anything needing a heavy duty bentone based grease.

INSTA-LUBE sprays out of the can as a thin liquid. As the carrier evaporates, it quickly thickens and sets up into thick NLGI #2 grease. Superior cohesive, adhesive, clinging properties allows INSTA-LUBE to be used in wet conditions and allows it to be sprayed onto vertical surfaces without the fear of the product running off.

INSTA-LUBE lubricates moving parts to prevent wear, protects against rust, corrosion, and oxidation. Product contains no harmful chlorinated solvents.

Automotive/machine uses: Lubricate brake and gear shift mechanism, steering parts, hinges, latches, distributor cams, cables, tracks, gears, sprockets, chains, pumps, hinges, bearings and much more.

### **DIRECTIONS:**

- -Hold container upright 6 to 8 inches from the surface to be sprayed. Spray area to be treated liberally and allow sufficient time for complete penetration, 20 to 30 seconds.
- -For extremely rusted and corroded parts additional product made be used and tapping or heating may be required.
- -Note: when changing the spray nozzle or inserting the extension tube always point the arrow on the spray nozzle away from your face and eyes.

distributed by:

ARROW - MAGNOLIA INTERNATIONAL, Inc. 2646 Rodney Lane Dallas, Texas 75229 Toll Free: 800.527.2101 www.arrowmagnolia.com