

liquid water treatments

Since 1927, Arrow-Magnolia has helped people solve their cleaning and maintenance problems with the finest products available today.

ARROW-MAGNOLIA
INTERNATIONAL, INC



SINCE 1927

LSM-66

LIQUID DESCRIPTION:

LSM-66 is formulated with powerful degreasing and detergent properties which clean the vertical surfaces of lift stations, wet wells, and similar treatment facilities.

Lift stations and wet wells tend to accumulate sewage, oils, greases and soap deposits on the walls. These deposits reduce the volume capacity of wet wells and the decomposition of the waste emits offensive odors. LSM-66 is used to remove or reduce the accumulations and improve the efficiency of the system.

DIRECTIONS:

-LSM-66 is added to the wet well or lift station until a layer of 8 to 12 inches is floating on the surface.

-Cleaning and degreasing is accomplished by the rise and fall of the sides of the wet well or lift station.

-The seal of LSM-66 also helps control offensive odors that emit from the lift station.

-It is suggested that LSM-66 be added monthly or more often if the system demands.

HIGHLIGHTS

- Lift Station Maintainer
- Reduces Odors
- Cleans Vertical Surfaces of Lift Stations
- Bi Level Action

TYPICAL PROPERTIES

- Vapor Pressure: **4.80**
- Volatility: **100**
- Solubility: **Insoluble**
- Specific Gravity: **0.7773**
- Vapor Density: **Heavier**

than Air

- pH: **N/A**
- Evaporation Rate: **N/A**
- Physical Description: **Clear**

Blue-Green Liquid w/Solvent


Odor

SAFETY CAUTIONS

- Keep out of reach of children.
- Use non-sparking utensils when handling this material.
- Avoid hot metal surfaces.
- Use under normal atmospheric conditions in well ventilated areas.
- Keep containers closed when not in use.
- Refer to SDS for additional safety information.



HMIS RATINGS



manufactured by:

ARROW - MAGNOLIA INTERNATIONAL, Inc.
2646 Rodney Lane
Dallas, Texas 75229
Toll Free: 800.527.2101
www.arrowmagnolia.com