

# aerosol miscellaneous

Since 1927, Arrow-Magnolia has helped people solve their cleaning and maintenance problems with the finest products available today.

**ARROW-MAGNOLIA**  
**INTERNATIONAL, INC**



SINCE 1927

## MAGIC GASKET MAKER-CLEAR

### MISC. DESCRIPTION:

MAGIC GASKET MAKER is a silicone RTV sealant and adhesive that will bond, caulk, seal, fasten, insulate, protect and repair many types of materials. Because it's virtually unaffected by weather, temperature extremes, chemicals and aging, it offers unmatched performance even under the most severe operating conditions. This material also seals or replaces a wide range of cork, paper, asbestos, felt and metal gaskets. It works on flanges, cover plates, hose connections and threaded assemblies.

MAGIC GASKET MAKER CLEAR is effective for temperatures up to 325°F continuous and up to 375°F for short periods.

### DIRECTIONS:

- Remove old gaskets, all oil and grease, and dry the surface.
- Apply fingertip pressure to stem and lay a thin, even bead (1/16" to 1/8") to one mating surface, encircling all bolt holes.
- Allow bead to "skin" (approx. 15 minutes) before assembling parts.
- Assemble carefully and do not overtighten bolts.
- If tooling is needed complete within 5 minutes. Remove excess sealant immediately with dry paper towel or knife.
- IMPORTANT: If entire contents are not used extrude 3/8" of sealant beyond nozzle opening, when ready to reuse, twist and pull out cured plug.

### CONTENTS UNDER PRESSURE

distributed by:

ARROW-MAGNOLIA INTERNATIONAL INC  
2646 Rodney Lane  
Dallas, Texas 75229  
Toll Free: 800.527.2101  
www.arrowmagnolia.com

#### HIGHLIGHTS

- 100% Silicone Rubber
- Permanently Flexible
- Effective from -60°F to 375°F
- Won't Foul Oxygen Sensors
- Meets or Exceeds OEM Volatility Specifications

#### TYPICAL PROPERTIES

- Boiling Range: **N/A**
- Vapor Pressure: **<5**
- Volatility: **N/A**
- Solubility: **Yes**
- Specific Gravity: **1.03**
- Vapor Density: **N/A**
- pH: **N/A**
- Evaporation Rate: **N/A**
- Physical Description: **Clear**

#### Paste w/ Acid-Like Odor

#### SAFETY CAUTIONS

- Keep out of reach of children.
- Product forms acetic acid when exposed to water or humid air.
- Provide ventilation during use to control acetic acid exposure.
- Refer to SDS for additional safety information.

#### HMIS RATINGS

