

liquid polishes/protectants

Since 1927, Arrow-Magnolia has helped people solve their cleaning and maintenance problems with the finest products available today.

ARROW-MAGNOLIA
INTERNATIONAL, INC



SINCE 1927

HIGHLIGHTS

- Prevents Concrete Adhesion
- Semi Permanent
- Clear, Plasticized Barrier
- Will Not Stain Yellow

TYPICAL PROPERTIES

- Vapor Pressure: **N/A**
- Volatility: **N/A**
- Solubility: **Insoluble**
- Specific Gravity: **0.9113**
- Vapor Density: **Heavier than Air**
- pH: **N/A**
- Evaporation Rate: **Slower than Ether**
- Physical Description: **Clear Liquid w/Solvent Odor**

SAFETY CAUTIONS

- Keep out of reach of children.
- Use under normal atmospheric conditions in well ventilated areas.
- Keep containers closed when not in use.
- Refer to SDS for additional safety information.



HMIS RATINGS



PC-70

LIQUID DESCRIPTION:

This clear, plasticized coating is intended to be applied to concrete equipment to prevent the adhesion of concrete, cement, mortar or plaster to painted or unpainted surfaces.

As PC-70 protects, it provides a non-yellowing film which is hard, long lasting and extremely high gloss. Cured film is resistant to acid based chemicals used in the clean-up operation.

PC-70 may be applied to concrete and masonry equipment for the same long lasting protection. This protective barrier is rust resistant and impervious to moisture.

DIRECTIONS:

-Apply undiluted product to surface of clean equipment only. Best results are obtained using a roller or paint brush. Be certain to adequately cover all exposed surfaces. Allow to dry completely.

-For more protection and further enhancement of gloss, PC-70 may be applied over the cured film.

-Product coverage averages 250 square feet per gallon. Scratched or worn areas may be recoated without complete removal of coating.

manufactured by:

ARROW MAGNOLIA INTERNATIONAL, INC.
2646 Rodney Lane
Dallas, Texas 75229
Toll Free: 800.527.2101
www.arrowmagnolia.com

PP-5065/1021