

Since 1927, Arrow-Magnolia cleaning and maintenance problems with the finest products available today.

#### HIGHLIGHTS

- -Plastic & Rubber Safe
- -Excellent Wire Pulling Lubricant
- -Stops Sticking & Squeaking
- -USDA Approved H2
- -High Temperature Range

#### **TYPICAL PROPERTIES**

-Vapor Pressure: 60 PSIG @ 70°F -Volatility: N/A -Solubility: Insoluble 0.9412 -Specific Gravity: -Vapor Density: N/A -pH: N/A -Evaporation Rate: N/A -Physical Description: White

#### Foam Spray w/ No Odor

#### SAFETY CAUTIONS

- -Keep out of reach of children. -Do not puncture or incinerate containers.
- -Do not store at temperatures above 130°F.
- -Do not store near heat, sparks or open flame.

-Refer to SDS for additional safety information.









#### **SINCE 1927**

# SANITARY LUBRICANT

## **AEROSOL DESCRIPTION:**

SANITARY LUBRICANT is formulated especially for the sanitary requirements of food and poultry plants. Heat stable from -40°F to 392°F.

SANITARY LUBRICANT is ideally suited for lubrication of conveyor parts, rollers, guide rails, grid belts, cams, casters, gears, sprockets, stirrups, plungers, slides, chains and cables, dicers and slicers. Ideal for dairies, breweries, meat packing plants, restaurants, hospitals or canneries. Also an excellent wire pulling lubricant as the foaming action creates a better clinging action.

### \*When used according to label directions, this product is safe to use in USDA Inspected Meat and Food **Processing.**

## **DIRECTIONS:**

-Shake well before using. Remove cap and hold 8 to 10 inches from surface.

-Spray until desired area of lubrication is wet.

distributed by:

ARROW - MAGNOLIA INTERNATIONAL, Inc. 2646 Rodney Lane Dallas, Texas 75229 Toll Free: 800.527.2101 www.arrowmagnolia.com

LG-6220/1021