Since 1927, Arrow-Magnolia has helped people solve their cleaning and maintenance problems with the finest products available today. HIGHLIGHTS

-Superior Truck Coating/ Protectant -Water Proof -Prevents Rust -Non Staining (Clear) -Non Gumming -Protects Costly Equipment in Outside Storage

TYPICAL PROPERTIES

-Vapor Pressure: 64
-Volatility: 95%
-Solubility: Insoluble
-Specific Gravity: 0.797
-Vapor Density: Heavier
than Air
-pH: 1.8
-Evaporation Rate: Slower
than Ether
-Physical Description: Clear
Liquid w/ Alcoholic Odor
SAFETY CAUTIONS
-Keep out of reach of children.

-Keep out of reach of children.
-Use under normal atmospheric conditions in well ventilated areas.

-Keep containers closed when not in use.

-Refer to SDS for additional safety information.









SUPER COAT

LIQUID **DESCRIPTION:**

SUPER COAT is a perfected formulation of the Siloxanes designed to protect construction equipment. It is a clear, non-staining, water and weather resistant, non-gumming formulation.

SUPER COAT prevents rust as well as protects paint and costly equipment. SUPER COAT forms a base coating on the surface of the cab and body and prevents concrete, sand, gravel, salt, snow, lime, mortar, asphalt, etc. from adhering.

DIRECTIONS:

-Just spray on with any simple pressure sprayer and allow drying, then wipe with a soft cloth.

-Applying SUPER COAT is simple and easy; it is practically foolproof. Streaking or discoloration are impossible.

-To remove concrete deposits from your SUPER COAT protected trucks after use, rinse the truck with ARROW SOLV diluted with water from a pressure hose.

-Preparation of equipment: Clean grease, oil, dirt, etc. off with ARROW SOLV. Remove concrete with our concrete stripper. Allow equipment to dry thoroughly after rinsing with water.

-SUPER COAT dries to a slick, hard finish in about 15 minutes

manufactured by:

ARROW - MAGNOLIA INTERNATIONAL, Inc. 2646 Rodney Lane Dallas, Texas 75229 Toll Free: 800.527.2101 www.arrowmagnolia.com PP-***/1021